



## Tuprint Citilight

Coated paper backlit

### Technical information

Specification	Unit	Norm	Type			
Weight	g/m <sup>2</sup>	UNE 57014-74	135 ± 4%	150 ± 4%	170 ± 4%	200 ± 4%
Bulk	cm <sup>3</sup> /g	UNE 57009-70	0,99 ± 0,03	1,02 ± 0,03	1,04 ± 0,03	1,04 ± 0,03
Porosity	indicator	ISO 534	>40	>40	>40	>40
Absolute Moisture	%	UNE 570066-86/3	6,5 ± 0,5	6,5 ± 0,5	6,5 ± 0,5	6,5 ± 0,5
Whiteness	CIE	UNE 57005-90	90 ± 2	90 ± 2	90 ± 2	90 ± 2
Opacity	%	ISO 2471	97 ± 2	97 ± 2	97 ± 2	97 ± 2
Gloc ink 75°	%	JVNI-001	>70	>70	>70	>70

Poster paper coated one side for backlit and indoor advertising (excellent uniform transparency). Ideal for piezo inkjet printing, solvent, mild solvent, UV and latex based inks.



The data and product information in this data sheet are based on testing accomplished by manufacturer. The manufacturers of signs are aware of the specific printing processes and conditions which the product will undergo during printing, and of the specific conditions in which the product will be used. It is the manufacturer's responsibility to determine whether the product is suitable for its intended end-use.

[www.tuplex.pl](http://www.tuplex.pl)